

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 100277

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13019-20)

Point for the ¼ sec. cor. of sec. 25 only, on the E. bdy of T19S R9W, at midpoint between closing corners.

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd.

T 19 S
¼ S 25
R 9 W
1957

from which

A Maple 18" dia., bears N.75°W., 28 lks., mkd. ¼ S25 BT.

A Maple 18" dia., bears S.56°W., 41 lks. mkd. ¼ S25 BT.

Fd. OK, June 5, 1981 by L. Roberts - M 87-78

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23536)

The ¼ sec. cor. of sec. 25 only, T19S R9W monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd.

from which new bearing trees

An alder, 15" dia., bears S.57¼°W., 84.8 ft., mkd. ¼ S25 BT on the bark.

A maple, 29" dia., bears N.29°W., 30.5 ft., mkd. ¼ S25 BT on the bark.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.

An iron rod with International Paper Company sign is alongside the monument