

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 1 Page(s) 406-07)

A Maple 7" dia., 150 ft. up, which I mark for cor. to secs. 19 & 30, T19S R8W S19 on NE.; R19S R8W S30 on SE. faces, with 4 notches on N. and 2 notches on S. edges; from which
A Maple 10" dia., bears N.57°E., 29 lks. dist. mkd. T19S R8W S19 BT.
A Maple 8" dia., bears S.39½°E., 15 lks. dist. mkd. T19S R8W S30 BT.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13020)

The sec. cor., in the stump hole of an uprooted Maple 18" dia. with no marks remaining, determined at the intersection of the original plainly blazed lines; from which an original bearing tree is as follows:

A Maple 14" dia., bears N.27°E., 29 lks., with no scribe marks visible on opened blaze. (Rec. brg. N.57°E.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S	T 19 S
	S 19
	S 30
R 9 W	R 8 W
	1957

from which new bearing trees:

A Maple 15" dia., bears N.81½°E., 56½ lks. dist. mkd. T19S R8W S19 BT.

A Maple 14" dia., bears S.16½°E., 9 lks. dist. mkd. T19S R8W S30 BT.

Cor. is located 10 lks. W of a branch, 4 lks wide, course S.

Fd. OK, June 5, 1981 by L. Roberts - M 87-78

Cor. Fd. OK and used in BLM resurvey by John P. Farnsworth, Cadastral Surveyors, under Group #1976, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17470)

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23536-7)

The cor. of secs. 19 and 30 only, monumented with an iron post, 2" dia., firmly set, projecting 9 ins. above ground, with a brass cap (properly) mkd. continued next pg

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which an original bearing tree
A maple, 25" dia., bears N.27°E., 19.1 ft., with no marks visible on partially healed blaze.
and the bearing trees mkd. by Tillman, et al., in 1957-58
A maple, 18" dia., bears N.81½°E., 37.3 ft., with a healed blaze.
A maple, 20" dia., bears S.16½°E., 5.9 ft., with a healed blaze. (Record, 4.6 ft.)
An iron rod guard post is alongside the monument.

Fd. as per rec. 4/2024 - by T. Hostetter - C.S. 65/112-006