

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 443-44)

-----  
Intersect the W. bdy. of Tp. 19 S., R 8 W., at the closing cor. of secs. 24 & 25, established on former survey\*, which is a basalt stone 16x10x8 ins., 12" in the ground marked CC on W. face, with 2 notches on S. and 4 notches on N. edges; from which

A Fir 8" dia., bears N.25°W., 30 lks. dist. mkd. T19S R9W S24 BT.

A Fir 7" dia., bears S.37°W., 21 lks. dist. mkd. T19S R9W S25 BT.

(Cor. is 2.23 chs. S. of the ¼ sec. cor. on W. bdy. of sec. 19, T19S R8W)

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13020-21)

-----  
Point for the closing cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd: T 19 S T 19 S

CC S 24 S 19  
S 25

R 9 W R 8 W  
1957

from which

An Alder 10" dia., bears N.76½°W., 57 lks. dist. mkd. T19S R9W S24 CC BT.

An Alder 16" dia., bears S.33½°W., 17 lks. dist. mkd. T19S R9W S25 CC BT.

BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15434)

-----  
The closing cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. in 1957, from which bearing trees mkd. in 1957:

An Alder snag 16" dia., bears S.33½°W., 17 lks. dist. mkd. T19S R9W S25 CC BT. (Cont. Next Page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 100338

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Alder snag 10" dia., bears N.76½°W., 57 lks. dist. mkd.  
T19S R9W S24 CC BT.  
and new bearing trees:  
An Alder 18" dia., bears S.33°W., 53 lks., mkd. T19S R9W  
S25 CC BT.  
A Maple 15" dia., bears N.87¼°W., 105 lks. dist. mkd.  
T19S R9W S24 CC BT.

Cor. Fd. and tied in BLM resurvey by John P. Farnsworth,  
Cadastral Surveyor, under Group #1076, surveyed Sept.  
1981/April 1983 - DCSO Records, Vol. 45 Page(s) 17474-75