

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, T19-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 445)

Intersect the W. bdy. of Tp. 19 S., R 8 W., at the closing cor. of secs. 13 & 24, established on former survey*, which is a Fir post 3 ft. long, 4" sq., set 24" in the ground mkd. CC T19S R9W on W.; S24 on S.; and S13 on N. faces, with 3 grooves on N. and S. faces; from which

A Fir 7" dia., bears N.10°W., 23 lks. dist., mkd. T19S R9W S13 BT.

A Fir 7" dia., bears S.70°W., 12 lks. dist., mkd. T19S R9W S24 BT.

(This cor. is 2.45 chs. S. of the ¼ sec. cor. on W. bdy. of S.18, T19S R8W.)

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13023)

Point for the closing cor. of secs. 13 & 24, T19S R9W at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:

T 19 S T 19 S
CC S 13 S 18
S 24
R 9 W R 8 W
1957

from which

A Fir 18" dia., bears N.28½°W., 48 lks. dist. mkd. T19S R9W S13 CC BT.

A Fir 28" dia., bears S.78 3/4°W., 31 lks. dist. mkd. T19S R9W S24 CC BT.

BLM Resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept.1981/April 1983 - (DCSO records Vol. 45 Page(s) 17476)

The closing cor., monumented with an iron post 2" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1957, from which the remains of bearing trees mkd. by Tillman, etal (Cont. Next Page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 100437

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, T19-9

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A root hole bears S.78 3/4°W., 31 lks. dist., alongside of which is a down Fir 30" dia., with illegible scribe marks visible on partially healed blaze.
A root hole bears N.28½°W., 48 lks. dist.
and new bearing trees:
An Alder 6" dia., bears S.78°W., 32 lks. dist., mkd. T19S R9W S24 CC BT.
An Alder 4" dia., bears N.29½°W., 43 lks. dist., mkd. T19S R9W S24 CC BT.