

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 12 only, T19-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 449)

-----  
Intersect W. bdy. of T19S R8W at a point 2.67 chs. S. of the ¼ sec. cor. on W. bdy. of sec. 6.

Set a basalt stone 12x10x6 ins., 8" in the ground, for closing cor. of secs. 1 & 12 mkd. CC on W. face, with 5 notches on S. and 1 notch on N. edges; from which

An Alder 6" dia., bears N.15°W., 30 lks. dist. mkd. T19S R9W S1 BT.

An Alder 6" dia., bears S.32°W., 40 lks. dist. mkd. T19S R9W S12 BT.

Old cor. bears S., 9 lks. dist.; I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13027)

-----  
Point for the closing cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd. T 19 S\*T 19 S

CC  $\frac{S 1^*}{S 12^* S 6}$   
R 9 W\*R 8 W  
1957

from which

A Fir 23" dia., bears N.76°W., 12 lks. dist. mkd. T19S R9W S1 CC BT.

A Fir 10" dia., bears S.50°W., 31 lks. dist. mkd. T19S R9W S12 CC BT.

Fd. BC & BTs by R. Rice 2/2014 - M167-43

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.