

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 6 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 1 Page(s) 449-500)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face; from which

A Fir 14" dia., bears N.55°W., 10 lks. dist. mkd. ¼ S BT.

A Fir 16" dia., bears S.55°E., 22 lks. dist. mkd. ¼ S BT.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13027-28)

The ¼ sec. cor. of sec. 6 only, determined at record distance from each of the original bearing trees:

A Fir stump 18" dia., bears N.57°W., 10 lks. dist. with scribe marks BT visible on unhealed blaze. (Rec. brg. N.55°W.)

A Fir snag 24" dia., bears S.57°E., 22 lks. dist. with scribe marks ¼ S visible on opened blaze. (Rec. brg. S.55°E.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S

¼ S 6

R 8 W

1957

from which new bearing trees:

A Fir 20" dia., bears N.12 ¾°E., 32 lks. dist. mkd. ¼ S6 BT.

A Fir 32" dia., bears S.50½°E., 72 lks. dist. mkd. ¼ S6 BT.