

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & S. 6, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 460)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked ¼ S on N. face; from which
Fir 12" dia., bears N.15°E., 69 lks. dist. mkd. ¼ S BT.
Fir 10" dia., bears S.37°W., 50 lks. dist. mkd. ¼ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 505-06)

Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set post 4 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which
A Fir 14" dia., bears S.56°W., 40 lks. dist. mkd. ¼ S BT.
A Fir 20" dia., bears N.14½°W., 35 lks. dist. mkd. ¼ S BT

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12356)

The ¼ sec. cor. of secs. 6 and 31, determined at record bearing and distance from the original bearing tree:

A Fir 26" dia., bears S.56°W., 40 lks. dist. mkd. with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 24" in the ground, with brass cap mkd: ¼ S 31
S 6
1954

from which a new bearing tree:

A Fir 38" dia., bears N.42°W., 89 lks. dist. mkd. ¼ S31 BT

Corner report by Wayne Donovan, LS #2553 - May 19, 1993 - C.S. File 63/153-57

Found - 1954 GLO brass cap out of ground, Reset from existing bearing tree.

32" Fir bears S.56°W., 26.4 ft., healed face.

1954 BT, blow down.

(Cont. Next Page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & S. 6, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 9" Fir bears N.64°W., 18.2 ft., blazed and scribed
"¼ S31 BT"
5" Fir bears S.85°E., 20.5 ft., blazed and scribed
"¼ S6 BT"
9" Hemlock bears N.10°W., 26.8 ft., blazed and
scribed "¼ S31 BT"

BLM dependent resurvey by Edith M Forkner & Jason A
Lightbown, Cadastral Surveyors, under Group #2820, surveyed
Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23529)

The ¼ sec. cor. of secs. 6 and 31, perpetuated by Donovan, in
1993, monumented with an iron post, 1" dia., firmly set, in
a mound of stone, 2 ft. base, 2 ft. high, top projecting 10"
above the mound, with a brass cap (properly) mkd.
from which the remains of a BT mkd. by Collier in 1891
A fir, 39" dia., bears S.56°W., 26.4 ft., with a healed
blaze.
and the bearing trees mkd. by Donovan
A fir, 12" dia., bears S.88½°E., 20.6 ft., with a healed
blaze.
A hemlock, 19" dia., bears N.15°W., 27.3 ft., with a
healed blaze.
A fir, 15" dia., bears N.64½°W., 18.3 ft., with a healed
blaze.