

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 534)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which

A Cedar, 12" dia., bears S.65¼°W., 22 lks., mkd: ¼ S BT

A Fir, 18" dia., bears N.74½°E., 14 lks., mkd: ¼ S BT

Les Roberts, L.S. #1039 - For: International Paper Co. - Jan. 1985 - M 98-19 - C.S. File 58/293

Found - 18" burnt Fir stump, N.86°E., 9.2 ft., to face. Rec. N.74½°E., 9.2 ft., no marks visible.

26" Cedar stump, S.65¼°W., 14.5 ft., to face. Rec. S.65¼°W., 14.5 ft., negative scribing visible.

Set - 2½"x30" alum. pipe and cap. Buried purple magnetic marker under alum. pipe. Pipe set using face measure from orig. BTs. Cap mkd: "T19S R8W S30 ¼ + S31 1985 PLS 1039"

38" Fir stump, S.72°E., 29.7 ft., to RR spike (painted/alum. washer)

Metal fence post next to brass cap. Wired land survey monument sign to fence post.

Corner lies on steep North slope in newly logged unit.

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23540)

The ¼ sec. cor. of secs. 30 & 31, perpetuated by Roberts, in 1985; monumented with an aluminum post, 2½" dia., firmly set, projecting 1 in. above ground, with an aluminum cap mkd. from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N.87°E., 9.2 ft., no marks visible. (Record, N.74½°E.)

A cedar stump, 25" dia., bears S.65¼°W., 15.6 ft., with a healed blaze and a nail with a washer mkd. PLS 1039 in the face. (Record and to face, 14.5 ft.)

and the remains of a bearing tree mkd. by Roberts

A fir stump, 36" dia., bears S.74°E., 31.1 ft., with a railroad spike in the face.

and new bearing trees

A fir, 7" dia., bears N.30°E., 5.1 ft., mkd. ¼ S30 BT.

A fir, 9" dia., bears S.9°W., 15.7 ft., mkd. ¼ S31 BT.

A steel fence post with Land Survey Monument sign is alongside the monument.

New BTs have a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.