

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 30

Alias	Description

Les Roberts, L.S. #1039 - For: International Paper Co. - Jan. 1985 - M 98-19 - C.S. File 58/293

Set - 2½"x30" alum. pipe and cap. Buried purple magnetic marker under alum. pipe. Cap marked "T19S R8W S30 ¼ + Cor. 1985 PLS 1039".
1½" iron pipe and cap bears N.77°40'15"W., 8.98 ft. (Pipe set by International Paper Co. in 1959 during staff compass survey)
18" Fir, N.30°W., 19.9 ft., (painted/scribed/alum. washer)
54" Fir, N.89°E., 53.8 ft., (painted/scribed/alum. washer)
Metal fence post next to brass cap. Wired land survey monument sign to fence post.
Corner lies on top of flat ridge about 20 ft. south of gravel road.

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23541)

The center ¼ sec. cor. of sec. 30, established by Roberts, in 1985, and is accepted as the cor.; monumented with an aluminum post, 2½" dia., firmly set, projecting 4" above the ground, with an aluminum cap (properly) mkd. from which bearing trees mkd. by Roberts
A fir, 57" dia., bears N.88°E., 53.8 ft., with a double healed blaze.
A fir, 34" dia., bears N.30°W., 19.9 ft., with a healed blaze.
A steel fence post is alongside the cor.
From this cor., a point reported by Roberts as being established by International Paper in 1959 during a staff compass survey bears N.77°54'39"W., 9.06 ft.; monumented with an iron post, 1½" dia., firmly set, projecting 11" above the ground, with a brass cap mkd. with a dimple, and is not used for control in this survey.