

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

<p>GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 537)</p> <p>-----</p> <p>Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which</p> <p> A Cedar, 18" dia., bears S.70 1/4°E., 50 lks., mkd: 1/4 S BT</p> <p> A Fir, 48" dia., bears N.6°E., 35 lks., mkd: 1/4 S BT</p>	
<p>Sam F. Konnie - For: Swanson Bros. Lbr. Co. Feb. 8, 1967 - C.S. File 55/26</p> <p>-----</p> <p>Found - Both (orig.) BTs are rotted down almost to ground level. No stake could be fd. No scribing visible.</p> <p>Set - 1" pipe, 24" long, 18" into the ground for the 1/4 sec. cor.</p> <p> Drove a 3/8"x8" spike into a 56" Fir stump. Spike is N.77 1/2°E., 41.5 ft from 1/4 corner.</p> <p> Drove a 3/8"x8" spike into a 40" Fir tree. Spike is S.56 1/2°E., 63.9 ft., from the 1/4 corner.</p>	
<p>Les Roberts, L.S. #1039 - For: International Paper Co. - Jan. 1985 - M 98-19 - C.S. File 58/293</p> <p>-----</p> <p>Found - 1 1/4"x18" threaded bolt with nut buried 6" below ground.</p> <p> 1"x26" iron pipe set by Sam Konnie in Feb. 1967.</p> <p> 24" Cedar stump, S.72°E., 33.0 ft., no marks, 1891 BT., rec. S.70 1/4°E., 33.0 ft.</p> <p> 48" double Fir, N.6°E., 23.0 ft., no marks, 1891 BT., rec. N.6°E., 23.1 ft.</p> <p> 40" downed Fir, S.56°E., 64.0 ft., no spike, 1967 BT., rec. S.56 1/2°E., 63.9 ft.</p> <p> 54" Fir stump, N.78°E., 41.2 ft., to spike, 1967 BT, rec. N.77 1/2°E., 41.5 ft.</p> <p>Set - 2 1/2"x30" alum. pipe and cap. Buried purple magnetic marker under alum. pipe. Place 1" pipe and 1 1/4" threaded bolt beside alum. pipe. Cap marked "T19S R8W S19 1/4 + Cor. 30 1985 PLS 1039".</p> <p> 54" Fir stump, N.78°E., 41.2 ft. to 3/8' spike (painted/alum. washer)</p> <p> Fir root collar, N.10°E., 17.3 ft. to RR spike (painted/alum. washer)</p> <p> Metal fence post next to brass cap. Wired land survey monument sign to fence post.</p> <p>Corner lies on steep South slope about 120 ft., North of East-West draw.</p>	
<p>continued next page</p>	

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23542)

The ¼ sec. cor. of secs. 19 and 30, perpetuated by Konnie, in 1967; subsequently perpetuated by Roberts in 1985; monumented with an aluminum pipe, 2½" dia., firmly set, projecting 2" above ground (alongside of which is an iron bolt, 1¼" dia., with a nut, firmly set, with top flush with the surface of the ground, and an iron pipe, 1" dia., firmly set, with top flush with the surface of the ground), with an aluminum cap (properly) mkd.

from which the remains of an original bearing tree
A very decayed cedar stump, size indeterminate, bears S.70¼°E., 33.0 ft., no marks visible.

and the remains of a bearing tree mkd. by Konnie
A decayed fir stump, 53" dia., bears N.76°E., 44.0 ft., no marks visible & a nail at chest height facing the cor.

and an accessory set by Roberts
A railroad spike set in a root collar bears N.8½°E., 17.2 ft., with washer mkd. PLS 1039 nailed alongside the spike.

and new bearing trees
A fir, 13" dia., bears N.53¾°E., 9.5 ft., mkd. ¼ S19 BT.

A fir, 9" dia., bears S.58¾°W., 18.7 ft., mkd. ¼ S30 BT.
A steel fence post with Land Survey Monument sign is alongside the monument.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.

Fd. Alum cap, 3 BTs, and RR spike. 4/2020 by R Cook - M176-67
New RM 1/2"x24" rebar with orange plastic cap stamped "CONTROL POINT" lies N.62°49'13"E 32.07 ft.

Fd. as per rec. 4/2024 - by T. Hostetter - C.S. 65/112-006