TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 540)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 40" dia., bears S.77°E., 32 lks., mkd: ¼ S BT
A Fir, 30" dia., bears N.77°W., 35 lks., mkd: ¼ S BT

Eugene Dist. of BLM - Transit and tape survey by Wayne Tinglum, Mark Lichtenthaler, Larry Smith & Michael Bilderback - Completed Oct. 1974 - M 57-31

Set - 3/4" iron rod from orig. BTs.

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17721)

The ¼ sec. cor of secs. 18 & 19, determined from the orig. BTs:
A Fir, 64" dia., bears S.77°E., 32 lks., with healed blaze.
A Fir, 58" dia., bears N.77°W., 35 lks., with scribe marks 4 S visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T19S R8W
¼ S 18 / S 19
1980

Set a 6 ft. steel fence post alongside the iron post.

Les Roberts, LS 1039 - For: International Paper Co. - March 1982 - M 91-73

CONDITION REPORT ONLY
Found - 1980 BLM BC, not of rec.
48" Fir bears N.77°W., 24.1 ft., (scribe visible) 1891 BT
62" Fir bears S.77°E., 23.3 ft., (scribe visible) 1891 BT
Note - Survey M 57-31 shows a 3/4" IR set, find no evidence of rod.