

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Eugene Dist. of BLM - Transit and tape survey by Wayne Tinglum, Mark Lichtenthaler, Larry Smith & Michael Bilderback - Completed Oct. 1974 - M 57-31

- 
- Set - 3/4" iron rod from which:
- A 26" Fir, bears N.36½°W., 48.1 ft.
  - A 35" Fir, N.26 3/4°E., 41.0 ft.
  - A 15" Fir, bears S.77¼°E., 31.2 ft.

-----

Les Roberts, L.S. #1039 - Nov.4, 1985 - C.S. File 63/50-12

- 
- Found - 3/4" iron pin set firmly in ground.
- 16" Fir, S.77°E., 31.0 ft. (scar vis.) 1974 BT rec. S.77¼°E., 31.2 ft.
  - 28" Fir, N.36°W., 48.0 ft. (scar vis.) 1974 BT Rec. N.36½°W., 48.1 ft.
  - 36" Fir, N.28°E., 41.4 ft., (scar vis) 1974 BT. Rec. N.26 3/4°E., 41.0 ft.

Set additional R.P.s because of planned logging activity in near future.

- 24" Alder, S.54°E., 8.80 ft. to RR spike in base of tree.
- 36" Fir, N.31°E., 39.60 ft. to RR spike in base of tree.

Corner lies on NE slope about 150 ft. North of road.

-----

Les Roberts, L.S. #1039 - Nov. 26, 1986 - C.S. File 63/50-13

- 
- Found - 3/4" iron pin set by BLM in 1974 was destroyed by recent logging.
- 16" Fir, S.77°E., 31.0 ft. (scar vis.) 1974 BT rec. S.77¼°E., 31.2 ft.
  - 28" Fir stump, N.36°W., 48.0 ft. (scar vis.) 1974 BT Rec. N.36½°W., 48.1 ft.
  - 36" Fir stump, N.28°E., 41.4 ft., (scar vis) 1974 BT. Rec. N.26 3/4°E., 41.0 ft.

- 24" Alder, S.54°E., 8.80 ft. to RR spike in base of tree. Set 11/04/1985
- 36" Fir, N.31°E., 39.60 ft. to RR spike in base of tree. Set 11/04/1985

Set - 2"x36" aluminum pipe and cap using distances of 8.80 ft. and 39.60 ft. from RR spikes set on 11/04/1985. Buried purple magnetic marker under 36" pipe. Set metal fence post, with survey attention sign wired to, beside aluminum pipe. Painted all BTs red.

Corner lies on NE slope about 150 ft. North of road.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Les Roberts, L.S. #1039 - Sept. 2, 1989 - C.S. File 63/50-11  
-----

- Found - 1986 I.P. alum. pipe & cap. Corner is in logged unit
- 16" Fir stump, S.77°E., 31.0 ft. (scar vis.) 1974 BT rec. S.77¼°E., 31.2 ft.
  - 28" Fir stump, N.36°W., 48.0 ft. (scar vis.) 1974 BT Rec. N.36½°W., 48.1 ft.
  - 36" Fir stump, N.28°E., 41.4 ft., (scar vis) 1974 BT. Rec. N.26 3/4°E., 41.0 ft.
  - 24" Alder, S.54°E., 8.80 ft. to RR spike in base of tree. 1985 R.P.
  - 36" Fir, N.31°E., 39.60 ft. to RR spike in base of tree. 1985 R.P.

Soaked sides & tops of stumps with a wood preservative.  
Covered tops of stumps with 0.020 thick sheets of aluminum.  
24" Alder stump not treated or covered.