

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 545)  
-----  
Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which  
    A Fir, 20" dia., bears N.12°E., 25 lks., mkd: 1/4 S BT  
    A Fir, 10" dia., bears S.29°W., 19 lks., mkd: 1/4 S BT

Oregon State Board of Forestry - Thomas W. Ray, District Eng. - D.O. Bryant, Witness - June 8, 1976 - C.S. File 58/31  
-----  
Orig. - Post (now missing) from which a:  
    20" Fir, N.12°E., 25 lks., now 28" Fir with face closed & BLM tag affixed. (N.25°E., 16.5)  
    10" Fir, S.29°W., 19 lks., now 10" snag with BLM tag affixed, exposed scribing 4S (S.15°W., 12.5 ft.)  
Set - Set 1 1/2" x 36" galv. IP with bronze cap mkd: "OREGON STATE BD. OF FORESTRY T19S R8W 1/4 S6 S7 1976 RS 563" 6" in ground, in mound of rock.  
from which  
    18" Fir S.50°W., 8.9 ft to face scribed 1/4 S7 BT RS563.  
No trees within limits in Sec. 6.  
Set - 4"x4"x60' WPCP 5.0 ft. NW of corner pipe. Oregon St. Forestry Dept. metal location poster on 18" Fir BT.

Corey Woodruff - For: Plum Cr. Timberland - 5/2009 - M159-30  
-----  
Found - 1976 OSBF BCIP in Rock mound.  
    22" D.Fir snag bears S.50°W., 8.9'  
    20" D.Fir bears (N.12°E.) is down.  
    10" D.Fir bears (S.29°W.) is down.  
BT mkd - 6" D.Fir bears N.16°E., 24.1'

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.