

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T20-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO recs Vol 1 Pg 460)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 5, 6, 31 and 32, marked T19S S32 on NE.; R8W S5 on SE.; T20S S6 on SW.; S31 on NW. faces, with 5 notches on E. and 1 on W. edges; from which

Fir 20" dia., bears N.33°E., 38 lks. mkd. T19S R8W S32 BT.
 Fir 20" dia., bears S.54°E., 20 lks. mkd. T20S R8W S5 BT.
 Fir 24" dia., bears S.9°W., 26 lks. mkd. T20S R8W S6 BT.
 Fir 20" dia., bears N.35°W., 45 lks. mkd. T19S R8W S31 BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 505)

Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

400 ft. above stream. Set post 4" sq., 4 ft. long, 24" in ground for cor. to secs. 31, 32, 5 & 6, marked T19S S32 on NE.; R8W S5 on SE.; T20S S6 on SW.; S31 on NW. faces, with 1 notch on West and 5 notches on E. edges; from which

A Fir 30" dia. bears N.36½°E., 43 lks. mkd T19S R8W S32 BT
 A Fir 12" dia., bears S.71¼°E., 32 lks mkd. T20S R8W S5 BT
 A Fir 18" dia., bears S.14¾°W., 34 lks mkd T20S R8W S6 BT.
 A Fir 24" dia., bears N.4°W., 35 lks. mkd. T19S R8W S31 BT

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12355)

The sec. cor., determined at record bearing and distance from the remaining original bearing trees:

A Fir 40" dia., bears N.36½°E., 43 lks. mkd. with a healed blaze.
 A Fir 20" dia., bears S.14¾°W., 34 lks. with marks T20S R8W S6 uncovered.

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T	19	S	R	8	W
	S	31	S	32	
	S	6	S	5	
	T	20	S		
	1954	continued next page			

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which new bearing trees;
A Fir 40" dia., bears N.12°E., 70 lks. mkd T19S R8W S32 BT
A Fir 33" dia., bears S.33¼°E., 81 lks. mkd T20S R8W S5 BT
A Fir 53" dia., bears S.18¼°W., 43 lks. mkd T20S R8W S6 BT
A Fir 70" dia., bears N.50½°W., 63 lks mkd T19S R8W S31 BT

Ronald L Rice - For: Oxbow Timber 1 LLC - Nov. 2015 - M170-30

Found - GLO brass cap dated 1954 w/the following accessories:
40" Fir snag bears N.36½°E., 28.4', no marks.
40" Fir snag bears N.12°E., 46.2', no marks.
Record 33" fir bearing S.33¼°E. down out of position
70" fir stump bears N.50½°W., 41.6' scribing visible
New BTs- 10" D.Fir bears N.50°E., 30.3', blazed, scribed T19S
R8W S32 BT
18" D.Fir bears S.51°E., 21.8', blazed, scribed T20S
R8W S5 BT
13" D.Fir bears S.42°W., 21.5', blazed, scribed T20S
R8W S6 BT
10" D.Fir bears N.32°W., 10.0', Blazed, scribed T19S
R8W S31 BT.
Steel post adjacent to corner.

Fd as per M170-30 12/2016 by R. Rice - C.S. file 65/96-2

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23528)

The cor. of secs. 5, 6, 31, & 32, perpetuated by Rice, in 2016, monumented with an iron post 2½" dia., firmly set, projecting 10" above the ground, with a brass cap (properly) mkd.
from which the remains of a tree mkd. by Collier in 1891
A fir snag, 28" dia., bears N.36½°E., 28.4 ft., with no marks visible on burned blaze.
and the remains of BTs mkd. by Tillman, et al., in 1953-54
A fir snag, 27" dia., bears N.12°E., 46.2 ft., no marks visible.
A fir stump, 46" dia., bears N.50½°W., 41.6 ft., with illegible scribe marks visible on open blaze.
and the bearing trees mkd. by Rice
A fir, 10" dia., bears N.49°E., 30.4 ft., with scribe marks T19S R8W S32 BT visible on open blaze.
A fir, 18" dia., bears S.53¼°E., 22.1 ft., with scribe marks T20S R8W S5 BT visible on open blaze.
A fir, 14" dia., bears S.41¼°W., 21.5 ft., with scribe marks T20S R8W S6 BT visible on open blaze. cont.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T20-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 10" dia., bears N.30¼°W., 10.0 ft., with scribe marks T19S R8W S31 BT visible on open blaze.