

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 532-3)

A dogwood, 10" dia., which I mark for ¼ sec. cor., ¼ S on W face; from which

A fir, 36" dia., bears N.78°E., 34 lks., mkd: ¼ S BT.

A cedar, 12" dia., bears N.80°W., 44 lks., mkd: ¼ S BT.

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23537)

The ¼ sec. cor. of secs. 31 & 32, determined by proportionate measurement; there is no remaining evidence of the original corner.

At the corner point

Set a brass tablet, 3¼" dia., 3½" stem, epoxied in a drill hole 4" deep, in bedrock, with top mkd.

T19S R8W

¼
S 31|S 32
2016

from which

A fir, 18" dia., bears S.59¾°W., 7.8 ft., mkd. ¼ S31 BT.

A fir, 23" dia., bears N.55½°E., 24.3 ft., mkd. ¼ S32 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.

Deposit a magnet in the drill hole.