

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 535)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which
 A Fir, 30" dia., bears N.64 3/4°E., 41 lks., mkd: ¼ S BT
 A Fir, 30" dia., bears N.77°W., 19 lks., mkd: ¼ S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17721)

The ¼ sec. cor. of secs. 29 & 30, determined from the remains of the orig. BTs:
 A Fir, 55" dia., bears N.64 3/4°E., 41 lks., with scribe mark S visible on opened blaze.
 A root hole, bears N.77°W., 19 lks.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
 T19S R8W
 ¼
 S 30 | S 29
 1980
from which a new BT:
 A Fir, 6" dia., bears S.52¼°W., 33 lks., mkd: ¼ S30 BT.
Set a 6 ft. steel fence post alongside the iron post.

Fd. Ok by Les Roberts Jan. 1985 - M 98-19

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23542-3)

The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 2½" dia., firmly set, flush with the top of a mound of stone, 2 ft. base, 12" high, with a brass cap (properly) mkd. from which an original bearing tree
 A fir, 67" dia., bears N.64¾°E., 27.1 ft., with a healed blaze.
and a bearing tree mkd. by Fisher and Mattson in 1980
 A fir, 19" dia., bears S.52¼°W., 22.5 ft., with a healed blaze.
A steel fence post with a USFS sign is alongside the monument.

Fd. BC & 2 BTs 4/2020 by R Cook - M176-67
Fd. as per rec. 4/2024 - by T. Hostetter - C.S. 65/112-006

