

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 535)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 19, 20, 29, & 30 mkd T19S S20 on NE, R8W S29 on SE, S30 on SW and S19 on NW faces, with 5 notches on E and 2 notches on S edges; from which
A fir 48" dia., bears N.32¾°E., 63 lks., mkd: T19S R8E S20 BT.
A cedar, 48" dia., bears S.62½°E., 48 lks., mkd: T19S R8E S29 BT.
A cedar, 30" dia., bears S.59°W., 30 lks., mkd: T19S R8E S30 BT.
A cedar, 10" dia., bears N.41½°W., 53 lks., mkd: T19S R8E S19 BT.

Robert Cook - For: Oxbow Timber 1 LLC - 4/2020 - M176-67

Set - 5/8" rod with 2" aluminum cap stamped "T19S R8W S19 S20 S28 S29 LS 2336 2019" by double proportion on a steep Northeast slope about 100' West of a ravine.
14" Cedar N.11°E 52.3 ft. scribed T19SR8WS20" above "BT".
20" D.Fir N.33°W., 30.8 ft. scribed "T19SR8WS19"BT" (scribes face West)
10" D.Fir S.51°W. 8.4 ft scribed T19SR8WS30" above "BT"
20" Maple North 99.9 ft scribed "X" above "BT"

Fd. as per rec. 4/2024 - by T. Hostetter - C.S. 65/112-006