

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 538)  
-----  
Set post, 3 ft. long, 3" sq., 24" in ground, for ¼ sec. Cor. Mkd ¼ S on W face; from which  
    A cedar, 18" dia., bears N.7°E., 23 lks., mkd: ¼ S BT.  
    A fir, 30" dia., bears N.20°W., 57 lks., mkd: ¼ S BT.

Robert A. Cook - For: Oxbow Timber 1 LLC - 4/2020 - M176-67  
-----  
Set - 5/8" iron rod and aluminum cap stamped "¼ S20 S 19 2020 T19S R8W" at the distance-distance intersection from the found original bearing tree stumps. Corner lies on a steep NE slope and a foot SW of a 30" sandstone slab.  
Found - 36" D.Fir stump N.22°W., (N.20°W.) 37.62 ft (57 lks.) with scribing visible "S 1".  
        18" Cedar stump N.04°E. (N.7°E.) 15.18 ft (23 lks.) no marks.  
Set RM - 1/2"x24" rebar with yellow cap "NSTAR" N.32°04'49"W 35.07 ft.  
New BTs- 7" D.Fir N.19°E., 6.2 ft. scribed "¼S20" above "BT".  
        17" D.Fir N.64°W., 13.7 ft. scribed "¼S19" above "BT".  
        15" D.Fir S.28°W., 18.0 ft scribed "¼S19" above "BT"