

PRIMARY CORNER DESCRIPTION Cor Secs 17, 18, 19, & 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 538)

300 ft. below ridge, Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 17, 18, 19, & 20, marked T19S S17 on NE, R8W S20 on SE, S19 on SW, S18 on NW faces, with 5 notches on E and 3 notches on S edges; from which

- A Fir, 7" dia., bears N.55 3/4°E., 115 lks., mkd: T19S R8W S17 BT.
- A Maple, 8" dia., bears S.67 1/2°E., 97 lks., mkd: T19S R8W S20 BT.
- A Cedar, 24" dia., bears S.85°W., 61 lks., mkd: T19S R8W S19 BT.
- A Cedar, 24" dia., bears N.66 1/4°W., 60 lks., mkd: T19S R8W S18 BT.

Les Roberts, LS 1039 - For: International Paper Co. - March 1982 - M 91-73

Found - 48" Cedar snag bears N.66°W., 39.6 ft., no marks, 1891 BT

Set - 50" Cedar bears S.87°W., 40.3 ft., no marks, 1891 BT

Set - 1 1/2" x 36" IP & brass cap (4"x4"x36" square post bears N.4°E., 6.0 ft.)

Note - Slope dist. used to re-set the corner.

Robert A. Cook - For: Roseburg Forest Products - 1/2021 - M179-6

Found - 2 1/2" brass cap per Survey M91-73, up 6" on a steep NE slope. A creek flowing NW lies about 70 ft North and 70 ft East. Blazed and posted lines run S, W, and E Cedar BT's found are measured in slope distance per M 91-73

50" Cedar snag S.87°W., 40.3 ft with evidence of 1982 chop marks, but no original evidence, with paint and tags.

Cedar remains/snag N.66°W 39.6 ft. mostly gone but I painted and tagged it.

New BT - 15" Pistol butt Hemlock N.50°W., 30.6 ft scribed "T19SR8WS18" above "BT" and 60d nail set directly above the center of the tree where it leaves the ground.

RM: = 1/2"x24" rebar with yellow cap "N.STAR" S.00°18'00"E., 232.12 ft.