

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 543-4)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 5, 6, 7, & 8, marked T19S S5 on NE, R8W S8 on SE, S7 on SW, S6 on NW faces, with 5 notches on E & S edges; from which
An Alder, 18" dia., bears N.14°E., 24 lks., mkd: T19S R8W S5 BT.
A Maple, 8" dia. bears S.60°E., 38 lks mkd: T19S R8W S8 BT
An Alder, 8" dia., bears S.41°W., 43 lks., mkd: T19S R8W S7 BT.
A Vine Maple, 4" dia., bears N.42°W., 50 lks., mkd: T19S R8W S6 BT.

Oregon State Board of Forestry - Thomas W. Ray, District Eng. D.O. Bryant, Witness - June 8, 1976 - C.S. File 58/31

Orig. - Post (now missing) from which a:
18" Alder N.14°E., 24 lks., now a 30" stump with tree rotted off.
8" Maple, S.60°E., 38 lks., now 21" with face open and old axe work visible.
8" Alder, S.41°W., 43 lks., now missing.
4" Vine maple, N.42°W., 50 lks., now missing.
Stream 3 lks., wide, course East, bears South 6 chains (now 520 ft.)
Ridge West 7.25 chs., course East & West, with broad top (now 700 ft.)
Set - Set 1½" x 36" galv. IP with bronze cap mkd:"OREGON STATE BD. OF FORESTRY T19S R8W S6 S7 S8 S5 1976 RS563" 6" in ground, in mound of rock. From which
20" Hemlock, S.26°W., 63.9 ft. to face; scribed T19S R8W S7 BT RS563.
20" Maple, N.19°W., 64.6 ft. to face; scribed T19S R8W S6 BT.
72" Fir, N.11°E., 75.6 ft. to face; scribed in bark T19S R8W S5 BT.
No trees within limits in SE quadrant.
Set - 4"x4"x60' WPCP 5.0 ft. NW of corner pipe. Oregon St. Forestry Dept. metal location poster on orig. 8" Maple BT. Also poster on 30" Fir stump West 370 ft. on East side of Dun Ridge Road.

Fd. BC, 5/2009 by Corey Woodruff, M159-30

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Rob Ward - 2/10/2010 (added 5/27/2021) - C.S. File 65/109-15 - Down loaded from Lane Co. Surveyor's Office (LCSO file number 41772

Found - OSBF cap 1976
72" Fir stump bears N.11°E., 75.6'
New - 14" Alder bears N.83°W., 25.1'
11" Alder bears N.17°W., 41.3'
Both scribed "T19S R8W S6 BT"

Lane Co Surveyors Office - Bruce Bothel & Stuart Duce - 3/14/2015 (added 5/27/2021) - C.S. 65/109-14 (Lane Index 16053)

Found - A 3" Brass cap (properly mkd) Cap facing south, 5" above the surface.
72" D.Fir stump with a tin cap, N.11°E., @ 75.9' to CTR. 1976
12" Alder with bark scribes N.17½°W., @ 41.3' to CTR 2010
16" Alder with bark scribes N.82½°W., @ 25.2' to CTR 2010
New - 8" Alder bark scribed "CSBT" S.39°E., @ 21.7' to CTR
5/8"x30" Rebar w/alum cap 'LCSO-RP1-2015" 2" above surface N.39½°E., @ 6.43'
Note - BTs: Distance shown is to an aluminum nail set at side/center of live trees.
GEOGRAPHIC MAP LOCATION: Not of survey grade accuracy
NAD 83/91 Values: LAT: N.43°56'12.3" LONG: W.123°40'45.1"

Robert A. Cook - For: Roseburg Forest Products - 4/2021 - M179-34

Found - 1976 Oregon State Board of Forestry brass cap on pipe up 5" per Lane Co. Corner Index 6372. Monument lies on SE slope & 0.55' NW of a "T" post riser.
2" Aluminum cap on 5/8" rod per Lane Co. Index 16053 N.40°31'56"E., 6.45 ft.
20" Alder N.16°W., 41.2 ft. (N.17°W., 41.3 per CS File 41772) with bark scribing.
72" D.Fir stump with tin lid N.13°E., 75.7 ft. (N.11°E., 75.6 per Index 6372).
Set - 11" D.Fir S.23°E., 64.5 ft. scribed "T19SR8WS8" above "BT".

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Please note this cor is on the County line & Lane Co. Surveyor's Office may have more information concerning this corner.