

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & S. 5, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 461)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N. face; from which
 Fir 20" dia., bears N.45°E., 29 lks. dist. mkd. $\frac{1}{4}$ S BT.
 Fir 20" dia., bears S.25°E., 40 lks. dist. mkd. $\frac{1}{4}$ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 505)

Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set post 4 ft. long, 4" sq., 24" in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N. face; from which
 A Fir 14" dia., bears N.53°W., 13 lks. dist., mkd. $\frac{1}{4}$ S BT.
 A Fir 14" dia., bears S.73°E., 13 lks. dist., mkd. $\frac{1}{4}$ S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12354)

The $\frac{1}{4}$ sec. cor., determined at record bearing from the original bearing trees:

 A Fir 19" dia., bears N.53°W., 15 lks. dist., marked with a healed blaze. (Rec. distance, 13 lks.)

 A Fir 10" dia., bears S.73°E., 15 lks. dist. with no marks remaining on blaze. (Record, A Fir, 14" dia., 13 lks.)

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$
1954

from which new bearing trees:

 A Fir 13" dia., bears N.2 $\frac{1}{2}$ °E., 36 lks. dist. mkd. $\frac{1}{4}$ S32 BT.

 A Cedar 18" dia., bears S.60°E., 64 lks. dist. mkd. $\frac{1}{4}$ S5 BT.

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & S. 5, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ron Rice - for: Oxbow Timber 1 LLC - Oct. 2014 - M168-56

Found - 1954 GLO brass cap with the following accessories:
19" D.Fir stump bears N.53°W., 9.9' - Healed face
10" Rotted D.Fir stump bears S.73°E. 9.9' - No marks
40" D.Fir stump bears N.2½°E., 23.4' - Healed face
26" Cedar bears S.60°E., 42.2' - Rotted open face
New BTs- 17" Hemlock bears N.37°W., 12.0' - blazed, scribed ¼
S32 BT
18" D.Fir bears N.37°E., 27.9' - blazed, scribed ¼
S32 BT
13" Alder bears S.74°W., 17.5' - blazed, scribed ¼
S5 BT
15" D.Fir bears S.18°E., 14.3' - blazed, scribed ¼
S5 BT.

Steel post adjacent to corner

Fd as per M168-56 12/2016 by R. Rice - C.S. file 65/96-2