

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 534)

Set post, 3 ft. long, 3" sq., 24" in ground, for ¼ sec. cor., marked ¼ S on N face; from which
A maple, 12" dia., bears N.35°W., 25 lks., mkd: ¼ S BT.
A fir, 30" dia., bears S.67½°E., 25 lks., mkd: ¼ S BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - Oct. 2015 - M170-25

Set - 5/8"x30" Rebar with 2½" aluminum cap marked as shown and established the following accessories:
9" D.Fir bears S.44°E., 36.3', blazed, scribed ¼ S32 BT
10" D.Fir bears N.88°W., 2.2', Blazed, scribed ¼ S29 BT
44" R.Cedar bears N.76°E., 7.1', blazed, scribed ¼ S29 BT.
11" D.Fir bears S.52°W., 16.0', Blazed, scribed ¼ S32 BT.

Steel post adjacent to corner

¼ $\frac{S29}{S30}$
2015
54633LS