

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 536)

Set Post, 3 ft. long, 3" sq., 24" in ground, for ¼ sec. Cor., marked ¼ S on N face; from which

A maple, 30" dia., bears S.15°E., 12 lks., mkd: ¼ S BT.

A maple, 24" dia., bears N.44°E., 48 lks., mkd: ¼ S BT.

Robert A. Cook - For: Oxbow Timber 1 LLC - 4/2020 - M176-67

Found - 1½" pipe with 2⅜" reducer filled with lead and not stamped. There was no record of this monument but it may have been set by Warren Hootman in the 50's for Crown Z, or IP. I obtained a copy of an unrecorded Bilderback survey, undated, that shows this pipe as "¾" Iron Pipe Painted red and BT". Position lies 30 ft. South of an old road and North of Cabin Creek.

A 1965 BLM tag on an Alder tree calls to the ¼ corner 30 feet South.

A 30" Maple windfall S.14°E., 8 ft, with 1965 BLM tag; may be the original tree but I cut it apart and found nothing.

I stamped the top of the cap "¼ S20 S29 2020".

New - I set a 1/2" x 24" rebar with yellow cap stamped "NSTAR" N.88°56'34"W., 137.66 ft.

24" D.Fir N.31°E., 77.6 ft. scribed "¼S20" above "BT".

28" D.Fir N.44°W., 72.7 ft. scribed "¼S20" above "BT".

15" Alder S.30°W., 18.1 ft. bark scribed "¼S29BT"