

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Corner Secs 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 539)

Set post, 3 ft. long, 3" sq., 24" in ground, for 1/4 sec. Cor. marked 1/4 S on N face; from which
 A fir, 10" dia., bears N.79°W., 41 lks., mkd: 1/4 S BT.
 A cherry, 5" dia., bears S.4°E., 19 lks., mkd: 1/4 S BT.

Robert A. Cook - For: Roseburg Forest Products - 1/2021 - M179-6

I searched for and did not find any evidence of the 1892 corner.
By single proportion measurement I set -
 5/8"x30" rebar with 2" aluminum cap stamped "NORTHSTAR SURVEYING" and "1/4 S17/S20 2021 LS 2336" in a mound of stone on a North slope. Monument lies about 100 ft North of a gravel rd.
New - RM = 1/2" x 24" rebar with yellow cap "N.STAR" S.88°40'34"E., 124.12 ft.
 22" Hemlock S.76°W., 90.0 ft. scribed "1/4 S20" above "BT".
 20" Hemlock N.68°W., 60.5 ft. scribed "1/4 S17" above "BT".
 13" D.Fir N.46°E., 89.5 ft. scribed "1/4 S17" above "BT".