

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 544)  
-----  
Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which  
    A Fir, 14" dia., bears S.21°E., 10 lks., mkd: 1/4 S BT  
    A Fir, 12" dia., bears N.32 1/2°W., 28 lks., mkd: 1/4 S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Pgs 17722-23)  
-----  
The 1/4 sec. cor. of secs. 5 & 8, determined from the remains of the orig. BTs:  
    A Fir, 38" dia., bears S.21°E., 10 lks., with scribe mark S visible in reverse and relief on overgrowth.  
    A root hole, bears N.32 1/2°W., 28 lks.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:  
                                    T19S R8W  
                                    1/4    S 5  
  S 8  
  1980  
from which a new BT  
    A Fir, 28" dia., bears N.44°E., 43 1/2 lks., mkd: 1/4 S5 BT.  
Set a 6 ft. steel fence post alongside the iron post.

Lane Co Surveyors Office - Bruce Bothel & Stuart Duce - 2/17/2015 (added 5/27/2021) - C.S. 65/109-13 (Lane Index 16003)  
-----  
Found - A 3 1/4" BLM brass cap (properly marked) atop a 2 1/2" iron post, 10" above ground.  
        A 38"x6' tall rotten fir stump with marks bears S.18°E., @ 7.1' to center (S.21°E., @ 10 LKS = 6.6'). 1891  
        31" D.Fir w/healed face N.44°E., @ 28.6' to CTR.  
New - 6" D.Fir marked "CSBT" N.49°14'W., @ 21.6' to CTR  
      5/8"x30" rebar w/2" alum cap "LCS0-RP1-2015", 10" below ground, 11' from CTR of RD S.6°29'W @ 93.63  
      5/8"x30" rebar w/2" alum cap "LCS0-RP2-2015", 10" below ground, 10' from CTR of RD N.87°23'W. @ 77.01'

Note - BTs: Distance shown is to an aluminum nail set at side/center of live trees.  
        Corner lies NE of BLM Gravel Rd 19-8-15.3  
Geographic map location: - not of survey grade accuracy NAD 83/91 VALUES: Lat: N 43°56'12.1" Long: W 123°40'08.8"

cont.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Robert A. Cook - For: Roseburg Forest Products - 4/2021 - M179-34

-----

Condition Report only

Found - 1980 BLM brass cap up 6" with a "T" post and sign North 2 ft.

8" D.Fir N.52°W., 21.5 ft. (N.49°14'W., 21.6 per Lane Index 16003).

38" D.Fir N.46°E., 28.4 ft. (N. 44°E., 43.5 lks. per 1980 BLM).

38" D.Fir high stump (S.21°E., 10 lks per 1891 GL0).