

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 20, 21, 28, & 29

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 526-7)

 Fir, 36" dia., which I mark for cor. to secs. 20, 21, 28 & 29 marked T19S S21 on NE, R8W S28 on SE, S29 on SW, S20 on NW faces, with 4 notches on E and 2 notches on S edges; from which


- A Fir, 18" dia., bears N.77°E., 29 lks., mkd: T19S R8W S21 BT.
- A Fir, 60" dia., bears S.63½°E., 50 lks., mkd: T19S R8W S28 BT.
- A Maple, 18" dia., bears S.18 3/4°W., 97 lks., mkd: T19S R8W S29 BT.
- A Maple, 16" dia., bears N.72°W., 50 lks., mkd: T19S R8W S20 BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12936)

(At N.0°25'E., 40.44 chains from the 1/4 Cor. of secs. 28 & 29) The cor. of secs. 20, 21, 28, & 29, which is marked with a Fir, 50" dia., showing healed blazes in each quadrant. The remaining BTs are:

- A Fir, 37" dia., bears N.72½°E., 29 lks., with an old blaze facing SW. (Rec. N.77°E.)
- A Fir, 70" dia., bears S.64¼°E., 54 lks., with an old blaze facing NW. (Rec. bearing S.63½°E., 50 lks.)

(At N.0°25'E., 40.38 chs from the 1/4 Cor. of secs. 28 & 29) Point for the witness to the cor. of secs.20, 21, 28, & 29. Set an iron post, 3' long, 1" dia., 27" in the ground, with brass cap mkd:



from which

- A Fir, 40" dia., bears N.31½°E., 101 lks., mkd: T19S R8W S21 BT.
- A Maple, 27" dia., bears S.80°E., 111 lks., mkd: T19S R8W S28 BT.
- A Alder, 10" dia., bears S.30°45'W., 77 lks., mkd: T19S R8W S29 BT.
- A Maple, 27" dia., bears N.65½°W., 53 lks., mkd: T19S R8W S20 BT.

Fd. Ok by W. Eimstad 4/1980 - M 84-77

Cont.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - For: Oxbow Timber 1 LLC - Oct. 2015 - M170-35

Found - GLO brass cap marked WC dated 1952
Original corner tree uprooted. The following accessories were fd:

Record corner tree accessories

- 37" Fir bearing N.72½°E., 19.1', down.
- 70" D.Fir snag bears S.64¼°E., 35.6' - no marks

New measurements to witness corner

- 70" D.Fir snag bears S.66½°E., 34.8' - no marks
- 40" D.Fir stump bears N.31½°E., 67.3' (record 66.7')
-scribing visible
- 37" Maple bears S.80°E., 73.3' - healed face
- 13" Alder bears S.30¾°W., 50.8' -bark scribe visible
- 28" Maple bears N.65½°W., 35.0' - healed face

Unrecorded bearing tree

- 74" D.Fir bears S.69½°W., 68.7' - healed face BLM tagged.
- Steel post adjacent to corner.

Fd. as per M170-25 9/2016 - R. Rice - C.S. File 65/94-5

Robert Cook - For: Oxbow Timber 1 LLC - 2/2018 - M174-18

Condition report

Found - 1952 GLO brass cap witness corner to uprooted corner tree. Corner lies N 0°25'E 3.96 ft. A steel post is adjacent to the corner.

- 70" D.Fir snag S.66°30'E. 34.8 ft., no marks.
- 40" D.Fir stump N.31°30'E. 67.3 ft. with scribing visible.
- 37" Maple S.80°E. 73.3 ft. healed blaze.
- 13" Alder S.30°45'W. 50.8 ft. with bark scribes.
- 28" Maple N.65°30'W. 35.0 ft. with healed blaze.
- 74" D.Fir S.69°30'W. 68.7 ft. with healed face.

Fd. BC & 6 BTs 4/2020 by R Cook - M176-67