

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 528)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 16, 17, 20, & 21, marked T19S S16 on NE, R8W S21 on SE, S20 on SW, & S17 on NW faces, with 3 notches on S and 4 notches on E edges; from which

A Fir, 18" dia., bears N.76 3/4°E., 49 lks., mkd: T19S R8W S16 BT.

A Fir, 18" dia., bears S.41°E., 25 lks., mkd: T19S R8W S21 BT.

A Fir, 24" dia. bears S.84°W., 29 lks mkd: T19S R8W S20 BT

A Fir, 24" dia. bears N.64°W., 23 lks mkd: T19S R8W S17 BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12938-39)

Point for the cor. of secs. 16, 17, 20, & 21 as determined from the two remaining orig. BTs:

A Fir, 32" dia., bears S.84°W., 29 lks., with an old blaze on E. face.

A Fir, 42" dia., bears N.64°W., 23 lks., with an old blaze on NE face.

At the corner point

Set an iron post, 3' long, 2" dia., 26" in the ground, with brass cap mkd:

T19S	R8W
S 17	S 16
S 20	S 21
1952	

from which

A Fir, 48" dia. bears N.32°E., 91 lks mkd: T19S R8W S16 BT

An Alder, 14" dia., bears S.73°45'E., 57 lks., mkd: T19S R8W S21 BT.

Ron Rice, NW Land Surveying - Sept. 2013 - C.S. File 65/80-3

Condition report only

Found - 1952 2½" GLO brass cap w/the following accessories

Fir, 32" dia., bears S.84°W., 29 lks., with an old blaze on E. face. (Down, rotted)

Fir, 42" dia., bears N.64°W., 23 lks., with an old blaze on NE face. (Fd 60" Fir with healed face)

Fir, 48" dia., bears N.32°E., 91 lks., mkd: T19S R8WSI6 BT. (Fd 69" Fir with healed face)

Alder, 14" dia., bears S.73°45'E., 57 lks., mkd: T19S R8WS21 BT. (Fd 19" Alder with rotted face)

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags, Compass decl. 16°E.

Robert A. Cook - For: Roseburg Forest Products - 1/2021 - M179-6

Found - 1952 GLO brass cap up 3" on East slope. Steel post North 6".

64" D.Fir N.31°E., 60.4 ft. with healed face, tag and paint, 1952 GLO record N.32°E., 91 lks.

60" D.Fir N.77°30'W., 12.4 ft. with healed face, tag and paint, 1952 GLO record N.64°W., 23 lks.

40" D.Fir snag S.82°20'W., 20.3 ft. with healed face, tag and paint, 1952 GLO record S.84°W., 29 lks.

New BT - 18" D.Fir S.81°40'W., 56.4 ft. scribed "T19SR8WS20" above "BT".