

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 530)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 16, 17, 8, & 9, marked T19S S9 on NE, R8W S16 on SE, S17 on SW, & S8 on NW faces, with 4 notches on E and S edges; from which

- A Fir, 36" dia., bears N.61°E., 75 lks mkd: T19S R8W S9 BT
- A Fir, 48" dia., bears S.29°E., 117 lks., mkd: T19S R8W S16 BT.
- A Fir, 20" dia., bears S.45½°W., 25 lks., mkd: T19S R8W S17 BT.
- A Fir, 36" dia., bears N.51°W., 30 lks mkd: T19S R8W S8 BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12941)

Point for the cor. of secs. 8, 9, 16, & 17 as determined from the orig. BTs:

- A Fir, 46" dia., bears N.61°E., 75 lks., with old blaze on SW face.
- A Fir, 60" dia., bears S.28½°E., 117 lks., showing old blaze facing NW (rec. S.29°E.)
- A Fir, 48" dia., bears S.46°W., 25 lks., with healed blaze on NE face. (Rec. S.45½°W.)
- A Fir, 48" dia., bears N.52½°W., 30 lks., with blaze facing SE. (Rec. N.51°W.)

At the corner point

Set an iron post, 3' long, 2" dia., 26" in the ground, with brass cap marked:

T19S R8W
S 8*S 9
S 17*S 16
1952

from which

- A Fir, 10" dia., bears N.42°45'E., 65 lks., mkd: T19S R8W S9 BT.
- A Fir, 16" dia. bears S.21°E. 32 lks. mkd: T19S R8W S16 BT
- A Fir, 10" dia. bears S.21°W. 55 lks. mkd: T19S R8W S17 BT
- A Fir, 11" dia., bears N.70°W., 60 lks mkd: T19S R8W S8 BT

Fd. Ok by D.Baker, 1/1984 - M 96-4

Ron Rice, NW Land Surveying - Sept. 2013 - C.S. File 65/80-5

Condition Report only

Found - 1952 2½" GLO brass cap w/the following accessories:
continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fir, 46" dia., bears N.61°E., 75 lks. with old blaze on SW face (Fd 72" Fir with healed face)
Fir, 60" dia., bears S.28WE., 117 lks., showing old blaze facing NW (Fd 60" Fir stump w/healed face)
Fir, 48" dia., bears S.46°W., 25 lks., with healed blaze on NE face (Fd 52" Fir with healed face)
Fir, 48" dia., bears N.52½°W., 30 lks., with blaze facing SE. (Fd 48" Fir stump with healed face)
Fir, 10" dia., bears N.42°45'E., 65 lks., mkd: T19S R8W S9 BT (Fd 15" Fir with healed face)
Fir, 16" dia. bears S.21°E. 32 lks. mkd: T19S R8W S16 BT (Fd 15" X 10' Fir stump with healed face)
Fir, 10" dia. bears S.21°W. 55 lks. mkd: T19S R8W S17 BT (Fd 21" Fir with healed face)
Fir, 11" dia., bears N.70°W., 60 lks., mkd: T19S R8W S8BT (Fd 17" Fir stump with healed face)
Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.
Compass Declination 16° East

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.