

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set silver magnetic marker on line and 5.0' in front
16" Fir bears S.73°33'W., @ 6.40' to nail in side
center (Rec. = S.72°W., @ 6.6')
Set blue magnetic marker 5.0' behind and on line
with corner.
New - No monuments set
1993 12" Fir bears S.69°02'E., @ 16.86' to nail at
side center, marked "CSBT"
SET PINK MAGNETIC MARKER 5.0' in front and on line
with corner.
5/8" iron rod with 2" aluminum cap, found flush with
ground, bears N.41°56'35"W., @ 390.62', mkd:
"LCSO LCCM 647 1992".
Witness post 1' SW'ly
Magnetic declination: 19¼°E.

Robert A. Cook - For: Roseburg Forest Products - 4/2021 -
M179-34

Found - 1952 GLO brass cap up 10" and "T" post South 1.8 ft.
20" D.Fir S.72°W., 6.6 ft. with healed face (1952
GLO)
22" D.Fir N.55°E., 25.7 ft. (N.55°30'E., 39 lks per
1952 GLO) healed face.
15" D.Fir S.69°E., 16.6 ft. (no record).
New - RM: 1/2" x 24" rebar with yellow cap "N.STAR"
N.19°29'00"E 31.32 ft.

Please note that this corner is on the Douglas Co. & Lane
Co. line and Lane Co. Surveyor's Office may have more
information concerning this corner.