

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4, T20-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 461-62)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for qr. sec. cor., marked ¼ S on N. face; from which
 Fir 40" dia., bears N.12°W., 35 lks. dist. mkd. ¼ S BT.
 Maple 18" dia., bears S.35°E., 51 lks. dist. mkd. ¼ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 504)

Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set stone 12x7x76 ins., 8" in ground for ¼ sec. cor. marked ¼ S on N. face; from which
 A Fir 36" dia., bears N.23°E., 87 lks. dist. mkd. ¼ S BT.
 An Alder 30" dia., bears S.22°E., 39 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12917)

Point for the ¼ sec. cor., as determined from the remains of the original bearing trees:

 A Fir 60" dia., bears N.23°E., 87 lks. dist. showing a healed blaze facing SW.
 A stump hole of an Alder bears S.22°E., 39 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, with brass cap mkd:

¼ $\frac{S \ 33}{S \ 4}$
1952

from which

 A Maple 10" dia., bears S.26½°E., 46 lks. dist. mkd. ¼ S4 BT.

Ron Rice, NW Land Surveying - April 2013 - C.S. File 65/78-28

Found - 1952 GLO brass cap with the following accessories:
 (Record 60" D.Fir N.23°E., 87 lks.) - down
 (Record 10" Maple S.26½°E 46 lks.) - missing

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4, T20-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

New -	18" Maple bears N.22°W., 22.9 ft. - blazed, scribed ¼ S33 BT
	17" D.Fir bears N.37°E., 28.7 ft. - blazed scribed ¼ S33 BT
	16" D.Fir bears S.44°E., 38.0 ft. - blazed scribed ¼ S4 BT
	20" D.Fir bears S.63°W., 19.8 ft. - blazed scribed ¼ S4 BT
Note -	Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Compass Declination 16° East