

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 525)

Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 40" dia., bears N.26°E., 45 lks., mkd: ¼ S BT
A Fir, 30" dia., bears S.75°W., 28 lks., mkd: ¼ S BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12934)

Point for the ¼ sec. cor. of secs. 28 & 33 as determined from the orig. BTs:

A Fir, 50" dia., bears N.26°E., 45 lks., mkd: ¼ S BT.

A Fir, 40" dia., bears S.75°W., 28 lks., showing old blaze facing E.

At the corner point

Set an iron post, 3' long, 1" dia., 27" in the ground, with brass cap mkd:

¼ $\frac{S\ 28}{S\ 33}$
1952

Fd. Ok by W. Eimstad 4/1980 - M 84-77

Ronald L Rice - For: Oxbow Timber 1 LLC - Dec. 2016 - M172-67

Found - GLO Brass cap dated 1952, with the following accessories:
52" D.Fir stump bears N.26°E., 29.7', healed face.
42" D.Fir stump with metal cap bears S.75°W., 18.5', healed face.

New - 13" D.Fir bears S.77°E., 4.9', blazed, scribed ¼ S33 BT.

12" D.Fir bears S.7°E., 21.7', blazed, scribed X BT.
Steel post adjacent to corner.