

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 462)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 33, 34, 3 & 4, marked T19S S34 on NE.; R8W S3 on SE.; T20S S4 on SW.; S33 on NW. faces, with 4 notches on W. & 2 on E. edges; from which
Fir 30" dia., bears N.43°E., 12 lks. dist. mkd. T19S R8W S34 BT.
Fir 20" dia., bears S.69°E., 24 lks. dist. mkd. T20S R8W S3 BT.
Fir 20" dia., bears S.86°W., 106 lks. dist. mkd. T20S R8W S4 BT.
Fir 36" dia., bears N.15°W., 20 lks. dist. mkd. T19S R8W S33 BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 503)

Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 33, 34, 3 & 4, marked T19S S34 on NE.; R8W S3 on SE.; T20S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges; from which
A Fir 30" dia., bears N.26½°E., 73 lks. dist. mkd. T19S R8W S34 BT.
A Fir 20" dia., bears S.49°E., 60 lks. dist. mkd. T20S R8W S3 BT.
A Maple 20" dia., bears S.49°E., (?) 60 lks. dist. mkd. T20S R8W S4 BT.
A Fir 48" dia., bears N.56 3/4°W., 77 lks. dist. mkd. T19S R8W S33 BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12916-17)

Point for the sec. cor., as determined from the remaining original bearing trees:
A Fir 40" dia., bears N.26½°E., 73 lks. dist., showing a healed blaze facing SW.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 40" dia., bears S.49°E., 60 lks. dist., with a healed blaze facing NW.

A Fir 66" dia., bears N.56°45'W., 77 lks. dist., with blaze facing SE.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T19S	R8W
S33	S34
S 4	S 3
T20S	
1952	

from which

A Hemlock 27" dia., bears S.55°45'W., 90 lks. dist. mkd. T20S R8W S4 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16717)

The sec. cor., monumented with an iron post 2" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1952, from which the remaining original bearing trees:

A Fir 42" dia., bears N.26½°E., 73 lks. dist., with healed blaze.

A Fir 42" dia., bears S.49°E., 69 lks. dist., with healed blaze. (Rec. 60 lks.)

A Fir 68" dia., bears N.54°W., 83 lks. dist., with healed blaze. (Rec. N.56 3/4°W., 77 lks.)

and the remains of the bearing tree marked in 1952:

A sawed Hemlock stump 28" dia., bears S.55 3/4°W., 90 lks. dist., with scribe marks T20S R8W S4 BT visible on open blaze.

Set a 6 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21754)

The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A metal capped fir stump, 46" dia., bears N.26½°E., 48.2 ft., no marks visible.

A fir, 62" dia., bears S.49°E., 45.5 ft., with a healed blaze.

continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T20-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir snag, 42" dia., bears N.54°W., 52.8 ft., with a healed blaze. (Record, 54.8 ft.) and the remains of the bearing tree mkd. by Lytle and Norseth in 1952

A decayed hemlock stump, 27" dia., bears S.55¼°W., 59.4 ft., no marks visible.

and new bearing trees

An alder, 5" dia., bears N.36°E., 18.7 ft., mkd. T19S R8W S34 BT on bark.

A fir, 9" dia., bears S.45°W., 4.8 ft., mkd. T20S R8W S4 BT.

A fir, 12" dia., bears N.8¼°W., 6.7 ft., mkd. T19S R8W S33 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Fd. as per rec. by Daniel Patterson, Cadastral surveyor (BLM) under Group #2305 surveyed March/April 2010 2011-2 PLAT and Vol. 59 PG 23653

Lat: 43°51'45.35"N Long: 123°38'21.25"W (NAD 1983 (COS 96))

Fd. BC, 7 BTs and 2 steel posts by Ron Rice - 4/2014 - M168-3

Fd. As per M168-3, 1/2015 D.Edwards, M170-32