

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 517)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 27, 28, 33, & 34, marked T19S S27 on NE, R8W S34 on SE, S33 on SW, S28 on NW faces, with 3 notches on S and 1 notches on S edges; from which

- A Fir, 40" dia., bears N.58 3/4°E., 79 lks., mkd: T19S R8W S27 BT.
- A Fir, 36" dia., bears S.80¼°E., 42 lks., mkd: T19S R8W S34 BT.
- A Fir, 24" dia., bears S.12°W., 108 lks., mkd: T19S R8W S33 BT.
- A Fir, 16" dia. bears N.2¼°W., 53 lks mkd: T19S R8W S28 BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12924-25)

The cor. of secs. 27, 28, 33, & 34 determined at the record bearing & distance from each of the orig. BTs, as follows:

- A Fir, 48" dia., bears N.58°45'E., 79 lks., showing a healed blaze facing SW.
- A Fir, 60" dia., bears S.80¼°E., 42 lks., showing a healed blaze facing W.
- A Fir, 40" dia., bears S.12°W., 108 lks., with a healed blaze facing N.
- A Fir stump bears N.2¼°W., 53 lks.

At the corner point

Set an iron post, 3' long, 2" dia., 27" in the ground, with brass cap mkd:

T19S	R8W
S 28	S 27
S 33	S 34
1952	

from which

- A Fir 8" dia., bears N.76°W., 64 lks. mkd: T19S R8W S28 BT

Fd. Ok 4/1980 W. Eimstad - M 84-77

David Edwards - For: Oxbow Timber 1 LLC - 1/2015 - M170-32

-
- Found - 76" fir S.80¼°E., 27.7' with healed blaze.
 - 30" Fir N.76°W., 42.2' with healed blaze.
 - New BT - 19" alder scribed "T19S R8W S33 BT" bears S.53°W., 10.4'
 - Set a six ft steel post 2 ft. south.