

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 519)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 21, 22, 27, & 28, marked T19S S22 on NE, R8W S27 on SE, S28 on SW, S21 on NW faces, with 3 notches on S and 2 notches on S edges; from which
A Fir, 24" dia. bears N.83°E., 71 lks mkd: T19S R8W S22 BT
A Fir, 7" dia. bears S.79½°E., 30 lks mkd: T19S R8W S27 BT
A Maple, 16" dia., bears S.42½°W., 52 lks., mkd: T19S R8W S28 BT.
A Fir, 14" dia. bears N.2½°W., 72 lks mkd: T19S R8W S21 BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12927)

Point for the cor. of secs. 21, 22, 27, & 28, determined from the two remaining BTs:
A Fir, 28" dia., bears N.83°E., 71 lks., showing a healed blaze facing SW.
A fir, 20" dia., bears S.79½°E., 30 lks., showing a healed blaze facing NW.
At the corner point
Set an iron post, 3' long, 2" dia., 27" in the ground, with brass cap mkd:

T19S	R8W
S 21	S 22
S 28	S 27
1952	

from which
A Fir, 42½" dia., bears S.67°W., 70 lks., mkd: T19S R8W S28 BT.
A Maple, 6" dia., bears N.45°W., 64 lks., mkd: T19S R8W S21 BT.

Ronald L Rice - Sept. 2016 - Oxbow Timber 1 LLC - C.S. File 65/94-5

Found - 1952 GLO brass cap with the following accessories:
60"x7' high D.Fir stump bears N.83°E., 46.9' - healed face.
42" D.Fir bears S.79½°E., 19.8' - no marks.
52" D.Fir bears S 67° W 46.2' - healed face
17" Maple bears N.45°W., 42.2' - no marks
Steel post adjacent to corner

continued next page

1

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2846, surveyed June 2016 - Nov. 2016 - (DCSO records Vol. 59 Page(s) 23814)

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.

from which the remains of BTs reported by Lytle & Norseth in 1952

A fir stump, 43" dia., bears N.83°E., 46.7 ft., with a healed blaze. (Original)

A fir, 43" dia., bears S.79½°E., 19.8 ft., no marks visible. (Original)

A fir, 52" dia., bears S.67°W., 46.2 ft., with a healed blaze.

A maple, 17" dia., bears N.45°W., 42.2 ft., with a healed blaze.

and a new BT

A fir, 6" dia., bears N.79°E., 5.4 ft., mkd. X BT.

A steel fence post is alongside the cor.

A search was made for all original line trees on the line resurveyed bet. secs. 27 and 28 and none were recovered.