

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs 15, 16, 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 521)

Set post, 4 ft. long, 4" sq., 24" in ground, for cor. to secs. 15, 16, 21, & 22, marked T19S S15 on NE, R8W S22 on SE, S21 on SW, S16 on NW faces, with 3 notches on E and S edges; from which
 A Maple, 6" dia., bears N.42½°E., 43 lks., mkd: T19S R8W S15 BT.
 A Fir, 20" dia., bears S.10°E., 33 lks., mkd: T19S R8W S22 BT.
 A Hemlock, 12" dia., bears S.79 3/4°W., 46 lks., mkd: T19S R8W S21 BT.
 A Maple, 7" dia., bears N.43½°W., 24 lks., mkd: T19S R8W S16 BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12928-9)

The point for the cor. of secs. 15, 16, 21, & 22 as determined from the remaining orig. BTs:
 A Fir, 36" dia., bears S.7¼°E., 33 lks, mkd: by a healed blaze on NW face. (Rec. bearing S.10°E.)
 A Hemlock, 26" dia., S.78°W., 46 lks., with healed blaze on NE face. (Record bearing S.79°45'W.)
At the corner
Set an iron post 3' long, 2' dia., 27" in the ground with brass cap mkd:
 T19S R8W
 S 16 | S 15
 S 21 | S 22
 1952
from which
 A Fir, 10" dia., bears N.39°45'E., 131 lks., mkd: T19S R8W S15 BT.
 A Fir, 42" dia., bears N.47°W., 138 lks., mkd: T19S R8W S16 BT.

Fd. by M. Krush, 11/11/1982 - M 93-36

Robert A. Cook - For: Oxbow Timber 1 LLC - 4/2020 - M177-1

Found - 2½" brass cap on 1½" pipe, 1952 GL0 up 7" on a West slope. All BTs are found.
 48" D.Fir N.50°W., (N.47°W.,) 96.6 ft. (138 lks.= 91.08 ft.) healed face and tag.
 34" Hemlock stump S.81°W., 29.2 ft. (S.78°W., 46 lks.) with healed face, tag and paint. Cont.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

48" D.Fir S.7°E., 22.9 ft. (S.7°15'E., 33 lks.) with healed face, tag and paint.
BT's tagged in 2016 per Pending USBLM Dependent Resurvey -
10" D.Fir S.48°W., 40.75 ft. with healed face, tag and paint.
10" Hemlock N.47°E., 29.2 ft. with healed face tag and paint.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2846, surveyed June 2016 - Nov. 2016 - (DCSO records Vol. 59 Page(s) 23815-6)

The cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with a brass cap (properly) marked.
from which the remains of BTs reported by Lytle & Norseth in 1952
A fir, 50" dia., bears S.7¼°E., 21.8 ft. with a healed blaze. (Original)
A hemlock stump, 27" dia., bears S.78°W., 30.4 ft. with a healed blaze. (Original)
A fir, 52" dia., bears N.47°W., 91.1 ft. with a healed blaze.

And new BTs
A hemlock, 10" dia., bears N.46½°E., 30.6 ft., mkd: T19S R8E S15 BT.
A fir, 11" dia., bears S.48½°W., 39.9 ft., mkd: T19S R8E S21 BT.