



TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T20-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16717)

-----  
The ¼ sec. cor. of secs. 3 & 34, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1952,

from which the original bearing trees:

A Fir 26" dia., bears N.10°W., 29 lks. dist., with healed blaze. (Rec. N.15°W.)

A Fir 30" dia., bears S.5°W., 15 lks. dist., with healed blaze. (Rec. S.12°W., 13 lks.)

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2305, surveyed March/April 2010 (added 12/5/2019 - (DCSO records Vol. 59 Page(s) 23653)

-----  
The ¼ sec. cor. of secs. 3 & 34, on the south bdy. of the township, monumented with an iron post, 1" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd from which the remaining original bearing tree

A fir, 38" dia., bears S.5°W., 9.9 ft., with a healed blaze.

and new bearing trees

A fir, 6" dia., bears N.89¼°W., 13.2 ft., mkd. ¼ S34 BT.

A hemlock, 7" dia., bears N.6½°W., 16.6 ft., mkd ¼ S34 BT.