

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 518)

Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which

An Alder, 20" dia., bears N.71 3/4°W., 30 lks. mkd: 1/4 S BT
A Vine Maple, 8" dia., bears S.7 1/2°W., 48 lks., mkd: 1/4 S BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12925)

Point for 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 3' long, 1" dia., 10" in the ground to bedrock and in a mound of stone to top, with brass cap mkd:

1/4 $\frac{S\ 27}{S\ 34}$

from which

An Alder, 12" dia., bears N.8 1/2°W., 87 lks., mkd: 1/4 S27 BT
A Cedar, 20" dia., bears S.24°E., 200 lks., mkd: 1/4 S34 BT