

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 511)

Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on W face; from which
A Cedar, 12" dia., bears N.12°W., 102 lks., mkd: 1/4 S BT
A Fir, 18" dia., bears N.4°E., 46 lks., mkd: 1/4 S BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12920-21)

The 1/4 secs. cor. of secs. 34 & 35, as determined from the one remaining orig. BT:

A dead Cedar, 14" dia., bears N.12°W., 102 lks, scribed 1/4 S BT.

At the corner point

Set an iron post, 3' long, 1" dia., 24" in the ground to solid rock, and in a mound of stone to top, with brass cap mkd:

1/4
S 34 | S 35
1952

from which

A Fir, 20" dia., bears N.70 1/2°E., 55 lks., mkd: 1/4 S35 BT.

A Fir, 27" dia., bears N.72 1/4°W., 35 lks., mkd: 1/4 S34 BT.

David Edwards - For: Oxbow Timber 1 LLC - 1/2015 - M170-32

Found - BLM brass cap
All previous BTs down

New BTs- 9" fir scribed "1/4 S35 BT" bears N.88°E., 11.7'

8" fir scribed "1/4 S34 BT" bears N.39°W., 5.60'

Set a 6 ft. steel post 2' north.