

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 512)

Set post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 26, 27, 34, & 35, marked T19S S26 on NE, R8W S35 on SE, S34 on SW S27 on NW faces, with one notch on S & 2 notches on E edges; from which

- An Alder, 24" dia., bears N.80½°E., 38 lks., mkd: T19S R8W S26 BT.
- A Vine Maple, 5" dia., bears S.37½°E., 49 lks., mkd: T19S R8W S35 BT.
- A Vine Maple, 4" dia., bears S.18°W., 60 lks., mkd: T19S R8W S34 BT.
- An Alder, 12" dia., bears N.2°W., 30 lks., mkd: T19S R8W S27 BT.

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12921)

Point for the cor. of secs. 26, 27, 34, & 35 as determined by the intersection of blazed lines N, S, E, & W, from which a stump hole of a fallen large Alder bears N.80½°E., 38 lks, evidently the position of the orig. NE BT; no evidence of the other bearing trees was recovered. At the corner

Set an iron post, 3' long, 2" dia., 28" in the ground, with brass cap mkd:

T19S	R8W
<u>S 27</u>	<u>S 26</u>
S 34	S 35

1952

from which

- An Alder, 11" dia., bears N.30½°E., 93 lks., mkd: T19S R8W S26 BT.
- A Fir, 77" dia., bears S.6¼°E., 362 lks., mkd: T19S R8W S35 BT.
- An Alder, 17" dia., bears S.23½°W., 211 lks., mkd: T19S R8W S34 BT.
- A Maple, 22" dia., bears N.70°W., 86 lks., mkd: T19S R8W S27 BT.

R. Wilson Hutchison - Wit. Ed Johnson - May 1960 C.S. File 51/97

Gov't Dependent Resurvey - brass cap in place.

- Alder 11" dia., N.30°30'E., 93 lks., (61.38') Gone
- Fir 77" dia., S.6°15'E., 362 lks., (238.92') High stump
- Alder 17" dia., S.23°30'W., 211 lks., (139.26') In
- Maple 22" dia., N.70°W., 86 lks., (56.76') IN

(Cont. next page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Remarked BT in Sec. 35:
Alder 12" dia., S.86°E., 26.3 ft. (Mkd. S35 BT)

Nov. 11, 1960 by Hutchison C.S. File 51/97 -
Remarked BT in Sec. 26
Maple 20" dia., N.60°E., 115.33 ft. (Mkd. CS BT)

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17707)

From the cor. of secs. 26, 27, 34, & 35, perpetuated by person(s) unknown, monumented with an iron bar, 5/8" dia, firmly set, the top 4" below surface of ground, from which the remains of BTs mkd. by Lytle & Norseth:

- A sawed Fir stump, 70" dia., bears S.5½°E., 366 lks., with scribe marks T19S R8 visible on partially healed blaze. (Rec. S.6¼°E., 362 lks.)
- A root hole, bears S.23¼°W., 211 lks., with a down Alder, 19" dia., alongside with healed blaze.
- A Maple, 28" dia., bears N.71¼°W., 86 lks., with healed blaze. (Rec. N.70°W.)

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, to solid rock, directly over the iron bar, in concrete, with brass cap:

T19S R8W	
S 27	S 26
S 34	S 35
1980	

- from which new BTs:
- An Alder, 8" dia., bears N.70½°E., 34 lks., mkd: T19S R8W S26 BT on bark.
 - An Alder, 11" dia., bears S.7°E., 192 lks., mkd: T19S R8W S35 BT on bark.
 - An Alder, 10" dia., bears S.24°W., 57 lks., mkd: T19S R8W S34 BT on bark.

Set a 6 ft. steel fence post alongside the iron post.
From this point, Esmond Creek, 20 lks., wide, bears South, 20 lks., course W.

FD BC & 3 BTs BY D.Baker 4/30/1985 - M 98-55 - C.S. File 58/289-4F

David Edwards - For: Oxbow Timber 1 LLC - 1/2015 - M170-32

Found - BLM brass cap
17" Alder, N.70½°E., 22.4' }all with
17" Alder S.7°E., 126.7' }partial bark CONT.

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set -	14" Alder S.24°W., 37.6' }scribes 6' steel post 2' south
Bob Cook - For: Roseburg Forest Products - 2/2020 - M176-52 -----	
Found -	1980 BLM brass cap on pipe flush with ground. Monument lies 8 feet north of the north bank of Esmond Creek and 130 feet south of main road. Steel post risers are 2 feet South and 1.2 feet North. RM set below lies 0.16 ft. North of line.
Set -	1/2" x 24" rebar with orange cap stamped "CONTROL POINT" S.88°03'54"E., 287.24 ft. 17" Alder S.7°E., 126.2 ft. with tag and paint. 14" Alder N.70°E., 22.6 ft. with tag and paint. 11" Alder (S.24°W. 37.67 seen down in creek with tag
----- -----	