

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 513)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 16" dia., bears N.28°E., 63 lks., mkd: ¼ S BT

A Fir, 30" dia., bears N.16½°W., 120 lks., mkd: ¼ S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17708)

Point for ¼ sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T19S R8W

S 27^¼ | S 26

from which

A Fir, 16" dia., bears S.58°E., 15 lks., mkd: ¼ S26 BT.

A Fir, 25" dia., bears S.35¼°W., 23 lks., mkd: ¼ S27 BT.

Set a 6 ft. steel fence post alongside the iron post.

FD BC & 2 BTs BY D.Baker 4/30/1985 - M 98-55 - C.S. File 58/289-4G