

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 516)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which
A Chittem, 7" dia., bears N.45°E., 7 lks., mkd: ¼ S BT
A Hemlock, 36" dia., bears S.19°W., 125 lks., mkd: ¼ S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17718)

The ¼ sec. cor. of secs. 14 & 15, perpetuated by person(s) unknown, monumented with a steel fence post, 6 ft. long, firmly set, projecting 18" above stream bed & debris, from which the remains of an orig. BT:
A Hemlock, 65" dia., bears S.19°W., 125 lks., with scribe marks BT visible on opened blaze.
and locally mkd. BTs
A Cedar, 21" dia., bears N.36°E., 67 lks., with scribe marks ¼ S14 BT visible on partially healed blaze.
A Maple, 33" dia., bears S.66°E., 80 lks., with scribe marks ¼ S14 BT visible on partially healed blaze.
A Cedar, 35" dia., bears N.4½°W., 168½ lks., with healed blaze.
and a reference monument
An iron post, 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.19°W., 40 lks., with brass cap mkd: T19S R8W ¼ S15 RM 40 LS 1980 and an arrow pointing to the corner.
Set a 6 ft. steel fence post alongside the reference monument.
The corner is located in creek, 4 lks., wide, course N.20°E.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2846, surveyed June 2016 - Nov. 2016 - (DCSO records Vol. 59 Page(s) 23805)

The ¼ sec cor of secs 14 & 15, determined at distance-distance intersection from the accessories reported by Fischer and Mattson in 1980
A hemlock, 65" dia., bears S.19°W., 82.5 ft., with no scribe marks visible on open blaze. (Original)
An iron post, 2½" dia., firmly set, with top 6" below the surface of the ground, bears S.19°00'00"W, 26.40 ft., with a brass cap mkd. T19S R8W RM 40 LKS TO COR ¼ S15 1980 and an arrow pointing to the cor.
Continued next page

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 46" dia., bears N.4½°W., 111.2 ft., with a healed blaze.

At the corner point Set an aluminum angle iron, 5 ft. long, 24" in the ground.

Corner is located in a creek, 10 ft. wide, course N.20°E.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.