

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 512-3)

Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which
 A Fir, 24" dia., bears S.41 1/2°W., 10 lks., mkd: 1/4 S BT.
 A Fir, 36" dia., bears N.3 1/2°E., 42 lks., mkd: 1/4 S BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12922)

The 1/4 secs. cor. of secs. 26 & 35, as determined from the orig. BTs:
 A Fir, 42" dia., bears N.4 1/2°E., 42 lks., with healed blaze facing nearly South. (Rec. bearing, N.3 1/2°E.)
 A Fir, 35" dia., bears S.41°W., 10 lks., with healed blaze facing north. (Rec. S.41 1/2°W.)
At the corner point
Set an iron post, 3' long, 1" dia., 24" in the ground to solid rock and in a mound of stone to top, with brass cap mkd:
$$\frac{1}{4} \begin{array}{l} \underline{S \ 26} \\ S \ 35 \\ 1952 \end{array}$$

from which
 A Hemlock 10" dia., bears N.15 1/4°E., 60 lks., mkd: 1/4 S26 BT
 A Fir, 42" dia., bears S.45°E., 48 lks., mkd: 1/4 S35 BT.

FD BC & 2 BTs BY D.Baker 4/30/1985 - M 98-55 - C.S. File 58/289-4E

Bob Cook - For: Roseburg Forest Products - 2/2020 - M176-52

Found - 1952 2 1/2" GLO brass cap on 3/4" pipe up 7" in Cedars and Hemlocks.
I set steel post as riser.
38" Hemlock N.16°E., 39.5 ft with healed face, tag and paint.