

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 514)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. or., mkd: ¼ S on N face; from which
 A Vine Maple, 2" dia., bears N.45°E., 18 lks., mkd: ¼ S BT
 A Fir, 4" dia., bears S.65°W., 150 lks., mkd: ¼ S BT.

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17709-10)

The ¼ sec. cor of secs. 23 & 26, determined from the remains of the orig. BTs:
 A clump of dead Vine Maple, bears N.45°E., 18 lks., no marks visible.
 A Fir snag, 58' dia., bears S.63½°W., 150 lks., with scribe marks ¼ visible on partially healed blaze. (Rec. S.65°W.)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
 T19S R8W
 ¼ $\frac{S23}{S26}$
 1980
from which new BTs:
 A Fir, 12" dia., bears S.11°W., 31 lks., mkd: ¼ S26 BT.
 A Fir, 15" dia., bears N.20½°W., 19 lks., mkd: ¼ S23 BT.
Set a 6 ft. steel fence post alongside the iron post.

FD BC & 3 BTs BY D.Baker 4/30/1985 - M 98-55 - C.S. File 58/289-4H

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.