TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 507-8)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which
A Maple, 14" dia., bears S.60½°E., 4 lks., mkd: ¼ S BT.
A Hemlock, 7" dia., bears N.36 3/4°W., 10 lks. mkd: ¼ S BT

BLM Resurvey by Marvin J. Lytle and Palmer Norseth, under Group #298, surveyed May/Aug. 1952 - (DCSO records Vol. 31 Page(s) 12919)

Point for ¼ sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 35 S 36
1952

from which
A Fir, 40" dia., bears N.5½°W., 32 lks., mkd: ¼ S35 BT.
A Fir, 17" dia., bears S.70½°E., 13 lks., mkd: ¼ S36 BT.

Richard Hintz - For: International Paper Co. - Dec. 1986 - M 103-6

Found - GLO 1" dia., iron pipe with brass cap protruding 10" above ground.
48" Fir bears N.6°W., 21.1 ft., healed blaze.
20" Fir (down) bears S.63°E., 14.3 ft. to center root hole.
New BTs- 23" Fir bears N.40°E., 62.0 ft. to spike, marked "¼ S36 BT"