

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 510)

 Set post, about 150 ft. below ridge, 4 ft. long, 4" sq. 24" in ground, for cor. to secs. 23, 24, 25, & 26, mkd: T19S S24 on NE, R8W S25 on SE, S26 on SW, S23 on NW faces, with 2 notches on S and 1 notch on E. edges; from which
 A Cedar, 24" dia., bears N.10°E., 41 lks., mkd: T19S R8W S24 BT.
 A Fir, 36" dia., bears S.77°E., 127 lks., mkd: T19S R8W S25 BT.
 A Fir, 30" dia., bears S.11½°W., 105 lks., mkd: T19S R8W S26 BT.
 A Fir, 50" dia., bears N.70½°W., 68 lks., mkd: T19S R8W S23 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #'s 350 & 417, Surveyed Sept/Oct 1958 - (DCSO records Vol. 29 Page(s) 12325-26)

 Beginning at the cor. of secs. 23, 24, 25, & 26, determined at record distance from each of the Orig. BTs, as follows:
 A burned Cedar snag, 10" dia., bears N.12½°E., 41 lks., with no marks remaining. (Rec. bearing N.10°E.)
 A Fir snag, 35" dia., bears S.77°E., 127 lks., with fragmentary scribe marks visible on burned and decayed blaze.
 A Fir snag, 32" dia., bears S.14°45'W., 105 lks., with scribe marks R8W visible on open blaze. (Rec. bearing S.11½°W.)
 A Fir snag, 52" dia., bears N.61½°W., 68 lks., with fragmentary scribe marks visible on burned blaze. (Rec. bearing N.70½°W.)

At the corner point
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
 T19S R8W
 S 23 | S 24
 S 26 | S 25
 1958

from which new BTs:
 A Fir, 16" dia. bears N.17°E. 66 lks. mkd: T19S R8W S24 BT
 A Fir, 6" dia. bears S.40°E. 23 lks. mkd: T19S R8W S25 BT
 A Fir, 15" dia. bears S.37°W. 14 lks. mkd: T19S R8W S26 BT
 A Fir, 6" dia., bears N.22½°W., 88 lks., mkd: T19S R8W S23 BT.

(Cont. next page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec 1980 - (DCSO records Vol. 46 Page(s) 17701-02)

The cor. of secs. 23, 24, 25, & 26, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with properly marked brass cap.

from which the remains of the orig. BTs:

A burned Cedar snag, 11" dia., bears N.12½°E., 45 lks., with no marks visible. (Rec. N.10°E., 41 lks.)

A rotted Fir stump, size indeterminate, bears S.77°E., 127 lks., no marks visible.

A Fir snag, 33" dia., bears S.14 3/4°W., 112 lks., with scribe marks R8W visible on open blaze. (Rec. 105 lks.)

A Fir snag, 46" dia., bears N.61½°W., 68 lks., with scribe marks T19S R8W visible on burned blaze.

and BTs mkd. by Brooks:

A Fir, 25" dia., bears N.15½°E., 95 lks., with healed blaze. (Rec. N.17°E., 66 lks.)

A Fir, 12" dia., bears S.40°E., 23 lks., with healed blaze.

A Fir, 23" dia., bears S.37°W., 14 lks., with healed blaze.

A Fir, 13" dia., bears N.22½°W., 88 lks., with healed blaze.

FD BC & 7 BTs BY D.Baker 4/30/1985 - M 98-55 - C.S. File 58/289-4J