

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 509)

-----  
Set post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which  
    An Alder, 12" dia., bears S.67°W., 52 lks., mkd: 1/4 S BT  
    A Fir, 14" dia., bears N.88°E., 12 lks., mkd: 1/4 S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors y under Group # 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17699)

-----  
Point for 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 19 S R 8 W

1/4  $\frac{S \ 25}{S \ 36}$

from which

    A Fir, 75" dia., bears N.75 1/4°E., 122 lks., mkd: 1/4 S25 BT.

    A Fir, 42" dia., bears S.66°E., 128 lks., mkd: 1/4 S36 BT.

Set a 6 ft. steel fence post alongside the iron post.