

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 511)

-----

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. or., mkd: ¼ S on N. face; from which

A Maple, 10" dia., bears N.7¼°W., 58 lks., mkd: ¼ S BT

An Alder, 18" dia., bears S.23½°W., 48 lks., mkd: ¼ S BT

BLM dependent resurvey by Lester E. Fisher & David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029, Surveyed Jan/Dec. 1980 - (DCSO records Vol. 2 Page(s) 17703)

-----

The ¼ secs. cor. of secs. 24 & 25, reestablished at proportionate distance and recorded by William A. Eimstad, RLS #377 (DCSO has no record of a survey setting this corner 2/4/1999) in 1979 and is accepted as the best available evidence of the position of the orig. corner, monumented with an iron bar 5/8" dia., firmly set, projecting 2" above ground, from which bearing trees mkd. by Eimstad.

An Alder, 20" dia., bears N.47°E., 17 lks., with scribe marks ¼ S24 BT visible on open blaze.

An Alder, 16" dia., bears S.8°E., 22½ lks., with scribe marks ¼ S25 BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

	T19S	R8W
_____ ¼	<u>S 24</u>	
	S 25	
	1980	

Set a 6 ft. steel fence post alongside the iron post.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.