

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 499-500)

At point on W. slope of ridge near top, about 350 ft. below table land.

Set post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 36 and 25, marked T19S R8W S25 on NW.; T19S R8W S36 on SW. faces, with 5 notches on N. and 1 notch on S. edge; from which

A Fir 10" dia., bears N.46 3/4°W., 79 lks. dist. mkd. T19S R8W S25 BT.

A Fir 10" dia., bears S.61½°W., 87 lks. dist. mkd. T19S R8W S36 BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 12951)

The cor. of secs. 25 & 36, determined at the record bearing and distance from each of the original bearing trees as follows:

A burnt Fir stump 20" dia., bears S.61½°W., 87 lks. dist., with blaze consumed.

A burnt Fir stump 20" dia., bears N.46°45'W., 79 lks. dist., with blaze consumed.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S	T 19 S
S 25	
S 36	R 7 W
R 8 W	S 31
1949	

from which new bearing trees:

A Fir 12" dia., bears S.53½°W., 50 lks. dist. mkd. T19S R8W S36 BT.

A Fir 10" dia., bears N.39¼°W., 42 lks. dist. mkd. T19S R8W S36 BT.

BLM resurvey by Lester E. Fisher and David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029 - Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17698-99)

The Sec. Cor., monumented with an iron post 2" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1949, from which bearing trees mkd. by Price & Tillman:

A Fir 20" dia., bears S.50°W., 52 lks. dist., with healed blaze. (Rec. S.53½°W., 50 lks.)

(Cont. Next Page)

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 15" dia., bears N.43½°W., 44 lks. dist., with healed blaze. (Rec. N.39¼°W., 42 lks.)
Set a 6 ft. steel fence post alongside the iron post.