

TOWNSHIP 19 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 500)

In a hollow, course NW., 300 ft. deep.
Set post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face; from which
A Maple 10" dia., bears S.54 3/4°W., 9 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears S.33½°E., 48 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 12952)

The ¼ sec. cor., determined at the record bearing and distance from each of the original bearing trees as follows:

A down Fir 16" dia., bears S.33½°E., 48 lks. dist., with blaze burned.

A Maple stump in Maple stool, 16" dia., bears S.54°45'W., 9 lks. dist., with blaze badly decayed.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ S 25
1949

from which new bearing trees:

A Fir 36" dia., bears S.80°45'W., 41 lks. dist. mkd. ¼ S25 BT.

A Fir 10" dia., bears N.7¼°W., 149 lks. dist. mkd. ¼ S25 BT.