

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 500)

Set post 4½ ft. long, 4" sq., 24" in the ground for cor. to secs. 24 & 25, marked T19S R8W S24 on NW.; T19S R8W S25 on SW. faces, with 2 notches on S. and 4 notches on N. edges; from which

- A Dogwood 6" dia., bears S.15°W., 26 lks. dist. mkd. T19S R8W S25 BT.
- A Laurel 10" dia., bears N.31½°W., 50 lks. dist. mkd. T19S R8W S24 BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 12953)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S	T 19 S
S 24	
S 25	R 7 W
R 8 W	S 30
1949	

from which

- A Fir 8" dia., bears S.4°W., 90 lks. dist., mkd. T19S R8W S25 BT.
- A Madrona 6" dia., bears N.26°W., 22 lks. dist. mkd. T19S R8W S24 BT.

Cor. Fd. OK in BLM resurvey by Lester E. Fisher and David W. Mattson, Cadastral Surveyors, under Group #'s 1000 & 1029 - Surveyed Jan/Dec. 1980 - (DCSO records Vol. 46 Page(s) 17702)